

PLP-3

3 Inch Label Barcode Printer



Feature:

- Support label space detection
- Provide Windows, Linux driver
- Push-button start, OLED status display
- Compatible with ESC/POS, TSPL, CPCL command set

Specification:

MODEL		PLP-3
Print	print mode	Thermal line printing
	Printing speed(Max)	50mm/s(thermal label); 90mm/s(thermal paper)
	Resolution	203 dpi (8dots/mm)
	Effective printing width	72mm
Paper supply method		Drop-in easy loading
Paper spec.	Paper Type	Thermal paper/Thermal label roll
	Paper Diameter	40mm(Max.)
	Paper Thickness	Thermal paper roll:0.055-0.1mm; Thermal label roll:0.10-0.12mm
	Paper Width	25-80mm
	Roll Core Inner Diameter	13mm(Min)
Paper supply method		Drop-in easy loading
Detection		Cover open, paper ending, paper gap
Reliability	TPH	50km(12.5% print ratio)
Barcode	1D	EAN-13,EAN-8,CODE39,CODE93, CODE128,CODEBAR,ITF,UPC A,UPC
	2D	QR CODE,PDF417
Text and graphic support		Figure,symbol,graph,curve, icon,multi-languages
Command		ESC/POS,TSPL,CPCL
Driver/SDK		Windows Driver, Linux Driver, Android SDK
Interface	Wire	Mini USB
	Wireless	Bluetooth2.0 and 4.0
Battery		2000mAh
Recharge adapter		12V,1A
Accessories	Standard accessories	Li-ion battery, AC adapter, USB cable,paper roll, user manual
	Optional accessories	Protective Case, CD,user manual
Temperature		Operating:-10 C ~50 C
		Storage:-20 C ~ 60 C
Humidity		Operating:10%RH~80%RH
		Storage:10%~90%RH

